## (19) World Intellectual Property Organization

International Bureau



## 

(43) International Publication Date 24 February 2005 (24.02,2005)

**PCT** 

(10) International Publication Number WO 2005/017546 A1

(51) International Patent Classification7:

G01R 33/07

(21) International Application Number:

PCT/NL2004/000573

- (22) International Filing Date: 13 August 2004 (13.08 2004)
- (25) Filing Language:

Dutch

(26) Publication Language:

English

(30) Priority Data:

1024114


15 August 2003 (15:08:2003) N

- (71) Applicant (for all designated States except US): SYS-TEMATIC DESIGN HOLDING B.V. [NL/NL]; 5 G. Motorenweg NL-2623 CR Delft (NL)
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): MIDDELHOEK, Martin, Guldo [NL/NL]; 233, John F Kennedylaan, NL-2285 All Rijswijk (NL). REITSMA, George, Pieter [NL/NL]; 5, Jan van Heusdenstraat, NL-2203 CH Noordwijk (NL).

- (74) Agent: VAN DER AREND, Λ., G., A.; Exter Polak & Charlouis B.V., P.O. Box 3241, NL-2280 GB Rijswijk (NL)
- (81) Designated States (unless otherwise indicated for every kind of national protection available): AH. AG. AL. AM. Al. AU. AZ. BA. BB. BG. BR. BW. BY. BZ. CA. CH. CN. CO. CR. CU. CZ. DH. DK. DM. DZ. EC. HE. EG. ES. FI. GB. GD. GE. GH. GM. HR. HU. HD. HL. IN. IS. JP. KE. KG. KP. KR. KZ. LC. LK. LR. LS. LT. LU. LV. MA. MD. MG. MK. MN. MW. MX. MZ. NA. NI. NO. NZ. OM. PG. PH. PL. PI. RO. RU. SC. SD. SE. SG. SK. SI. SY. IJ. TM. TN. TR. TT. TZ. UA. UG. US. UZ. VC. VN. YU. ZA. ZM. ZW.
- (84) Designated States (unless otherwise indicated for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SI, SZ, IZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, II, IM), European (AI, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, II, LU, MC, NI, PI, PI, RO, SE, SI, SK, IR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, MI., MR, NE, SN, TD, TG)

[Continued on next page]

(54) Title: METHOD AND APPARATUS FOR MEASURING A MAGNETIC FIELD BY USING A HALL-SENSOR



(57) Abstract: Method and apparatus for measuring an entity of a magnetic field using a Hall sensor which is provided with at least one Hall plate (101, 102, 103, 104) which has a pair of terminals (Al A2. Bl, B2) for supplying an excitation signal and a pair of terminals (Al, A2, Bl, B2) for reading a detection signal. an electric voltage being supplied to the Hall plate as excitation signal from a source (105) of negligible impedance, and an electric current, which represents the measured entity, being tapped off from the Hall plate as detection signal by a pick-up (108, 1098, 110) of negligible impedance

## WO 2005/017546 A1



## Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations' appearing at the beginning of each regular issue of the PCI Gazette